

CHAPTER 337
Safety and Equipment

- | | | | |
|--------|---|--------|--|
| 337.01 | Driving unsafe vehicles; vehicle bumpers and height. | 337.14 | Use of headlight beams. |
| 337.02 | Lighted lights; measurement of distances and heights. | 337.15 | Lights of less intensity on slow-moving vehicles. |
| 337.03 | Headlights on motor vehicles and motorcycles. | 337.16 | Number of lights; limitations on flashing, oscillating or rotating lights. |
| 337.04 | Tail light; illumination of rear license plate. | 337.17 | Focus and aim of headlights. |
| 337.05 | Rear red reflectors. | 337.18 | Motor vehicle and motorcycle brakes. |
| 337.06 | Safety lighting on commercial vehicles. | 337.19 | Horn, siren and theft alarm signal. |
| 337.07 | Obscured lights on vehicles in combination. | 337.20 | Muffler; muffler cutout; excessive smoke, gas or noise. |
| 337.08 | Red light or red flag on extended loads. | 337.21 | Rear-view mirror; clear view to front, both sides and rear. |
| 337.09 | Lights on parked or stopped vehicles. | 337.22 | Sign or poster upon windshield; windshield wiper. |
| 337.10 | Lights on slow-moving vehicles; emblem required. | 337.23 | Limited load extension on left side of passenger vehicle. |
| 337.11 | Spotlight and auxiliary lights. | 337.24 | Motor vehicle stop lights. |
| 337.12 | Cowl, fender and back-up lights. | 337.25 | Air cleaner required. |
| 337.13 | Display of lighted lights. | 337.26 | Materials used in windshields and windows. |
| | | 337.99 | Penalty. |

CROSS REFERENCES

See sectional histories for similar State law
 Warning devices for commercial vehicles disabled upon
 freeways - see Ohio R.C. 4513.28
 Use of stop and turn signals - see TRAF. 331.14
 Wheel protectors for commercial vehicles - see TRAF. 339.05
 Vehicles transporting explosives - see TRAF. 339.06
 Towing requirements - see TRAF. 339.07
 Use of studded tires and chains - see TRAF. 339.11
 Bicycle equipment - see TRAF. 373.05 et seq.
 Motorized bicycle lights and equipment - see TRAF. 373.10
 Slow moving vehicle emblem - see OAC Ch. 4507-13
 Vehicle lighting - see OAC Ch. 4501-15

337.01 DRIVING UNSAFE VEHICLES; VEHICLE BUMPERS AND HEIGHT.

(a) No person shall drive or move, or cause or knowingly permit to be driven or moved, on any street any vehicle or combination of vehicles which is in such unsafe condition as to endanger any person or property.

(b) Nothing contained in this Chapter shall be construed to prohibit the use of additional parts and accessories on any vehicle not inconsistent with the provisions of this Chapter.

(c) The provisions of this Chapter with respect to equipment on vehicles do not apply to implements of husbandry, road machinery, road rollers or agricultural tractors except as made applicable to such articles of machinery.
(ORC 4513.02.)

(d) No person shall operate upon any street or highway any motor vehicle that:

- (1) Was originally equipped with bumpers as standard equipment, unless the vehicle is equipped with bumpers equal to the original equipped when so operated.
- (2) Has a suspension system or body so modified that the height of any bumper on the vehicle varies more than three (3) inches from the original manufactured bumper height for the vehicle.
(ORC 4513.021.)

337.02 LIGHTED LIGHTS; MEASUREMENT OF DISTANCES AND HEIGHTS.

(a) Every vehicle upon a street or highway during the time from one-half (1/2) hour after sunset to one-half (1/2) hour before sunrise, and at any other time when there are unfavorable atmospheric conditions or when there is not sufficient natural light to render discernible persons, vehicles and substantial objects on the street or highway at a distance of one thousand (1,000) feet ahead, shall display lighted lights and illuminating devices as required by this Chapter for different classes of vehicles; except that every motorized bicycle shall display at such times lighted lights meeting the rules adopted by the Ohio Director of Highway Safety under Ohio R.C. 4511.521. No motor vehicle, during such times, shall be operated upon a street or highway using only parking lights as illumination.

(b) Whenever in this Chapter a requirement is declared as to the distance from which certain lights and devices shall render objects visible, or within which such lights or devices shall be visible, such distance shall be measured upon a straight level unlighted street under normal atmospheric conditions unless a different condition is expressly stated.

(c) Whenever in this Chapter a requirement is declared as to the mounted height of lights or devices, it shall mean from the center of such light or device to the level ground upon which the vehicle stands. (ORC 4513.03.)

337.03 HEADLIGHTS ON MOTOR VEHICLES AND MOTORCYCLES.

(a) Every motor vehicle, other than a motorcycle, shall be equipped with at least two (2) headlights with at least one (1) near each side of the front of the motor vehicle.

(b) Every motorcycle shall be equipped with at least one (1) and not more than two (2) headlights. (ORC 4513.04.)

337.04 TAIL LIGHT; ILLUMINATION OF REAR LICENSE PLATE.

(a) Every motor vehicle, trailer, semitrailer, pole trailer or vehicle which is being drawn at the end of a train of vehicles shall be equipped with at least one (1) tail light mounted on the rear which, when lighted, shall emit a red light visible from a distance of five hundred (500) feet to the rear, provided that in the case of a train of vehicles only the tail light on the rear-most vehicle need be visible from the distance specified.

(b) Either a tail light or a separate light shall be so constructed and placed as to illuminate with a white light the rear registration plate, when such registration plate is required, and render it legible from a distance of fifty (50) feet to the rear. Any tail light, together with any separate light for illuminating the rear registration plate, shall be so wired as to be lighted whenever the headlights or auxiliary driving lights are lighted, except where separate lighting systems are provided for trailers for the purpose of illuminating such registration plate. (ORC 4513.05.)

337.05 REAR RED REFLECTORS.

Every new motor vehicle sold after September 6, 1941, and operated on a street, other than vehicles of the type mentioned in Section 337.06 or a commercial tractor to which a trailer or semitrailer is attached, shall carry at the rear, either as a part of the tail lights or separately, two (2) reflectors of such size and characteristics and so maintained as to be visible at night from all distances within three hundred (300) feet to fifty (50) feet from the vehicle. (ORC 4513.06.)

337.06 SAFETY LIGHTING ON COMMERCIAL VEHICLES.

Buses, trucks, commercial tractors, trailers, semitrailers and pole trailers, when operated upon any street, shall be equipped with clearance lights, marker lights, reflectors and stop lights as required by State regulations. Such equipment shall be lighted at all times mentioned in Section 337.02 except that clearance lights and side marker lights need not be lighted on a vehicle operated where there is sufficient light to reveal any person or substantial object on the street at a distance of five hundred (500) feet.

Such equipment shall be in addition to all other lights specifically required by Section 337.02 to Section 337.15, inclusive. Vehicles operated under the jurisdiction of the Ohio Public Utilities Commission are not subject to this Section.

(ORC 4513.07.)

337.07 OBSCURED LIGHTS ON VEHICLES IN COMBINATION.

Whenever motor and other vehicles are operated in combination during the time that lights are required, any light, except tail lights, which by reason of its location on a vehicle of the combination would be obscured by another vehicle of the combination need not be lighted, but this Section does not affect the requirement that lighted clearance lights be displayed on the front of the foremost vehicle required to have clearance lights or that all lights required on the rear of the rearmost vehicle of any combination shall be lighted. (ORC 4513.08.)

337.08 RED LIGHT OR RED FLAG ON EXTENDED LOADS.

Whenever the load upon any vehicle extends to the rear four (4) feet or more beyond the bed or body of such vehicle, there shall be displayed at the extreme rear end of the load, at the times specified in Section 337.02, a red light or lantern plainly visible from a distance of at least five hundred (500) feet to the sides and rear. The red light or lantern required by this Section is in addition to the red rear light required upon every vehicle. At any other time there shall be displayed at the extreme rear end of such load a red flag or cloth not less than sixteen (16) inches square. (ORC 4513.09.)

337.09 LIGHTS ON PARKED OR STOPPED VEHICLES.

Except in case of an emergency, whenever a vehicle is parked or stopped upon a roadway open to traffic or shoulder adjacent thereto, whether attended or unattended during the times mentioned in Section 337.02, such vehicle shall be equipped with one (1) or more lights which shall exhibit a white or amber light on the roadway side visible from a distance of five hundred (500) feet to the front of such vehicle, and a red light visible from a distance of five hundred (500) feet to the rear. No lights need be displayed upon any such vehicle when it is stopped or

parked where there is sufficient light to reveal any person or substantial object within a distance of five hundred (500) feet upon such street. Any lighted headlights upon a parked vehicle shall be depressed or dimmed. (ORC 4513.10.)

337.10 LIGHTS ON SLOW-MOVING VEHICLES; EMBLEM REQUIRED.

(a) All vehicles other than bicycles, including animal-drawn vehicles and vehicles referred to in Section 337.01(c), not specifically required to be equipped with lights or other lighting devices by Sections 337.02 to 337.09, shall at all times specified in Section 337.02, be equipped with at least one (1) light displaying a white light visible from a distance of not less than one thousand (1,000) feet to the front of the vehicle, and shall also be equipped with two (2) lights displaying red light visible from a distance of not less than one thousand (1,000) feet to the rear of the vehicle, or as an alternative, one (1) light displaying a red light visible from a distance of not less than one thousand (1,000) feet to the rear and two (2) red reflectors visible from all distances of six hundred (600) feet to one hundred (100) feet to the rear when illuminated by the lawful lower beam of headlights. Every animal-drawn vehicle shall at all times be equipped with a slow-moving vehicle emblem complying with Subsection (b) hereof.

Lights and reflectors required by this Section shall meet standards adopted and promulgated by the Ohio Director of Highway Safety.

(b) All farm machinery and other machinery, including all road construction machinery, upon a street or highway, except when being used in actual construction and maintenance work in an area guarded by a flagman, or where flares are used, or when operating or traveling within the limits of a construction area designated by the Ohio Director of Transportation, or the Municipal or County Engineer, when such construction area is marked in accordance with requirements of the Director and the Manual of Uniform Traffic Control Devices, as set forth in Ohio R.C. 4511.09, which is designed for operation at a speed of twenty-five (25) miles an hour or less shall be operated at a speed not exceeding twenty-five (25) miles an hour, and shall display a triangular slow-moving vehicle emblem (SMV). The emblem shall be mounted so as to be visible from a distance of not less than five hundred (500) feet to the rear. The Ohio Director of Highway Safety shall adopt standards and specifications for the design and position of mounting the SMV emblem. The standards and specifications for SMV emblems referred to in this Section shall correlate with and, so far as possible, conform with those approved by the American Society of Agricultural Engineers.

(c) The use of this emblem shall be restricted to animal-drawn vehicles, and to the slow-moving vehicles specified in Subsection (b) hereof operating or traveling within the limits of the highway. Its use on slow-moving vehicles being transported upon other types of vehicles or on any other type of vehicle or stationary object on the highway is prohibited.

(d) No person shall sell, lease, rent or operate any slow-moving vehicle, as defined in Subsection (b) hereof, except those units designed to be completely mounted on a primary power unit, which is manufactured or assembled on or after April 1, 1966, unless the vehicle is equipped with a slow-moving vehicle emblem mounting device as specified in Subsection (b) hereof.

(e) The slow-moving vehicles specified in Subsection (b) hereof may, in addition to the use of the slow-moving vehicle emblem be equipped with a red flashing light which shall be visible from a distance of not less than one thousand (1,000) feet to the rear at all times specified in Section 337.02. When a double-faced light is used, it shall display amber light to the front and red light to the rear. (ORC 4513.11.)

337.11 SPOTLIGHT AND AUXILIARY LIGHTS.

(a) Any motor vehicle may be equipped with not more than one (1) spotlight and every lighted spotlight shall be so aimed and used upon approaching another vehicle that no part of the high-intensity portion of the beam will be directed to the left of the prolongation of the extreme left side of the vehicle, nor more than one hundred (100) feet ahead of the vehicle.

(b) Any motor vehicle may be equipped with not more than three (3) State approved auxiliary driving lights mounted on the front of the vehicle, which when used shall conform to State regulations. (ORC 4513.12.)

337.12 COWL, FENDER AND BACK-UP LIGHTS.

(a) Any motor vehicle may be equipped with side cowl or fender lights or lights on each side thereof which shall emit a white or amber light without glare.

(b) Any motor vehicle may be equipped with back-up lights, either separately or in combination with another light. No back-up lights shall be continuously lighted when the motor vehicle is in forward motion. (ORC 4513.13.)

337.13 DISPLAY OF LIGHTED LIGHTS.

(a) At all times mentioned in Section 337.02 at least two (2) State approved lighted lights shall be displayed conforming to State regulations, one (1) near each side of the front of every motor vehicle, except when such vehicle is parked subject to the regulations governing lights on parked vehicles. (ORC 4513.14.)

(b) However, on a motorcycle, there shall be displayed at least one (1) and not more than two (2) lighted lights as required herein.

337.14 USE OF HEADLIGHT BEAMS.

Whenever a motor vehicle is being operated on a roadway or shoulder adjacent thereto during the times specified in Section 337.02, the driver shall use a distribution of light, or composite beam, directed high enough and of sufficient intensity to reveal persons, vehicles and substantial objects at a safe distance in advance of the vehicle, except that upon approaching an oncoming vehicle, the lights or beams shall be so aimed that the glaring rays are not projected into the eyes of the oncoming driver.

(ORC 4513.15.)

337.15 LIGHTS OF LESS INTENSITY ON SLOW-MOVING VEHICLES.

Any motor vehicle may be operated under the conditions specified in Section 337.02 when it is equipped with two (2) lighted lights upon the front thereof capable of revealing persons and substantial objects seventy-five (75) feet ahead in lieu of lights required in Section 337.13, provided that such vehicle shall not be operated at a speed in excess of twenty (20) miles per hour.

(ORC 4513.16.)

337.16 NUMBER OF LIGHTS; LIMITATIONS ON FLASHING, OSCILLATING OR ROTATING LIGHTS.

(a) Whenever a motor vehicle equipped with headlights is also equipped with any auxiliary lights or spotlight or any other light on the front thereof projecting a beam of an intensity greater than three hundred (300) candle power, not more than a total of five (5) of any such lights on the front of a vehicle shall be lighted at any one time when such vehicle is upon a highway.

(b) Any lighted light or illuminating device upon a motor vehicle, other than headlights, spotlights, signal lights or auxiliary driving lights, which projects a beam of light of an intensity greater than three hundred (300) candle power shall be so directed that no part of the beam will strike the level of the roadway on which the vehicle stands at a distance of more than seventy-five (75) feet from the vehicle.

(c) Flashing lights are prohibited on motor vehicles, except as a means for indicating a right or left turn, or in the presence of a vehicular traffic hazard requiring unusual care in approaching, or overtaking or passing. This prohibition does not apply to emergency vehicles, road service vehicles servicing or towing a disabled vehicle, traffic line strippers, snow plows, rural mail delivery vehicles, vehicles transporting preschool children as provided in Ohio R.C. 4513.182, Ohio

Department of Transportation maintenance vehicles, funeral hearses, funeral escort vehicles and similar equipment operated by the Department or local authorities, which shall be equipped with and display, when used on a street or highway for the special purpose necessitating such lights, a flashing, oscillating or rotating amber light, but shall not display a flashing, oscillating or rotating light of any other color, nor to vehicles or machinery permitted by Section 337.10 to have a flashing red light.

(d) Except a person operating a public safety vehicle, as defined in Section 301.27. or a school bus, no person shall operate, move or park upon or permit to stand within the right of way of any public street or highway any vehicle or equipment which is equipped with and displaying a flashing red or a flashing combination red and white light, or an oscillating or rotating red light, or a combination red and white oscillating or rotating light; and except a public law enforcement officer, or other person sworn to enforce the criminal and traffic laws of the State or Municipality, operating a public safety vehicle when on duty, no person shall operate, move or park upon, or permit to stand within the right of way of any street or highway any vehicle or equipment which is equipped with, or upon which is mounted, and displaying a flashing blue or a flashing combination blue and white light, or an oscillating or rotating blue light, or a combination blue and white oscillating or rotating light. This Section shall not prohibit the use of warning lights required by law or the simultaneous flashing of turn signals on disabled vehicles. (ORC 4513.17)

337.17 FOCUS AND AIM OF HEADLIGHTS.

No person shall use any lights mentioned in Sections 337.02 to 337.16, inclusive, upon any motor vehicle, trailer or semi-trailer unless the lights are equipped, mounted and adjusted as to focus and aim in accordance with State regulations. (ORC 4513.19.)

337.18 MOTOR VEHICLE AND MOTORCYCLE BRAKES.

The following requirements govern as to brake equipment on vehicles:

(a) Every motor vehicle, other than a motorcycle, when operated upon a street or highway, shall be equipped with brakes adequate to control the movement of and to stop and hold such motor vehicle, including two (2) separate means of applying the brakes, each of which means shall be effective to apply the brakes to at least two (2) wheels. If these two (2) separate means of applying the brakes are connected in any way, then on such motor vehicles manufactured or assembled after January 1, 1942, they shall be so constructed that failure of any one (1) part of the operating mechanism shall not leave the motor vehicle without brakes on at least two (2) wheels.

(b) Every motorcycle, when operated upon a street or highway, shall be equipped with at least one (1) adequate brake, which may be operated by hand or by foot.

(c) Every motorized bicycle shall be equipped with brakes meeting the rules adopted by the Ohio Director of Highway Safety under Ohio R.C. 4511.521.

(d) Every trailer or semi-trailer, except a pole trailer, of a gross weight of two thousand (2,000) pounds or more, manufactured or assembled on or after January 1, 1942, when operated upon the streets or highways of this Municipality, shall be equipped with brakes adequate to control the movement of and to stop and to hold such vehicle and so designed as to be applied by the driver of the towing motor vehicle from its cab, and such brakes shall be so designed and connected that, in case of a breakaway of the towed vehicle, the brakes shall be automatically applied.

(e) In any combination of motor-drawn trailers or semi-trailers equipped with brakes, means shall be provided for applying the rearmost brakes in approximate synchronism with the brakes on the towing vehicle, and developing the required braking effort on the rearmost wheels at the fastest rate; or means shall be provided for applying braking effort first on the rearmost brakes; or both of the above means, capable of being used alternatively, may be employed.

(f) Every vehicle and combination of vehicles, except motorcycles and motorized bicycles, and except trailers and semi-trailers of a gross weight of less than two thousand (2,000) pounds, and pole trailers, shall be equipped with parking brakes adequate to hold the vehicle on any grade on which it is operated, under all conditions of loading, on a surface free from snow, ice or loose material. The parking brakes shall be capable of being applied in conformance with the foregoing requirements by the driver's muscular effort or by spring action or by equivalent means. Their operation may be assisted by the service brakes or other source of power provided that failure of the service brake actuation system or other power assisting mechanism will not prevent the parking brakes from being applied in conformance with the foregoing requirements. The parking brakes shall be so designed that when once applied they shall remain applied with the required effectiveness despite exhaustion of any source of energy or leakage of any kind.

(g) The same brake drums, brake shoes and lining assemblies, brake shoe anchors, and mechanical brake shoe actuation mechanism normally associated with the wheel brake assemblies may be used for both the service brakes and the parking brakes. If the means of applying the parking brakes and the service brakes are connected in any way, they shall be so constructed that failure of any one (1) part shall not leave the vehicle without operative brakes.

(h) Every motor vehicle or combination of motor-drawn vehicles shall be capable at all times and under all conditions of loading of being stopped on a dry, smooth, level road free from loose material, upon application of the service or foot brake, within the following specified distances, or shall be capable of being decelerated at a sustained rate corresponding to these distances:

	From a speed of 20 miles per hr.	
	Stopping distance	Deceleration
	in feet	in feet per second
Brakes on all wheels	30	14
Brakes not on all four (4) wheels	40	10.7

(i) All brakes shall be maintained in good working order and shall be so adjusted as to operate as equally as practicable with respect to the wheels on opposite sides of the vehicle.
(ORC 4513.20.)

337.19 HORN, SIREN AND THEFT ALARM SIGNAL.

(a) Every motor vehicle when operated upon a street shall be equipped with a horn which is in good working order and capable of emitting sound audible, under normal conditions, from a distance of not less than two hundred (200) feet.

(b) No motor vehicle shall be equipped with, nor shall any person use upon a vehicle, any siren, whistle or bell. Any vehicle may be equipped with a theft alarm signal device which shall be so arranged that it cannot be used as an ordinary warning signal. Every emergency or public safety vehicle shall be equipped with a siren, whistle or bell capable of emitting sound audible under normal conditions from a distance of not less than five hundred (500) feet and of a type approved by the Ohio Director of Highway Safety. Such equipment shall not be used except when such vehicle is operated in response to an emergency call or is in the immediate pursuit of an actual or suspected violator of the law, in which case the driver of the emergency or public safety vehicle shall sound such equipment when it is necessary to warn pedestrians and other drivers of the approach thereof. (ORC 4513.21.)

(c) No person shall use the horn of a motor vehicle except to give warning to other drivers or pedestrians.

337.20 MUFFLER; MUFFLER CUTOUT; EXCESSIVE SMOKE, GAS OR NOISE.

(a) Every motor vehicle and motorcycle with an internal combustion engine shall at all times be equipped with a muffler which is in good working order and in constant operation to prevent excessive or unusual noise, and no person shall use a muffler cutout, by-pass or similar device upon a motor vehicle on a highway. Every motorcycle muffler shall be equipped with baffle plates.

(b) No person shall own, operate or have in his possession any motor vehicle or motorcycle equipped with a device for producing excessive smoke or gas, or so equipped as to permit oil or any other chemical to flow into or upon the exhaust pipe or muffler of such vehicle, or equipped in any other way to produce or emit smoke or dangerous or annoying gases from any portion of such vehicle, other than the ordinary gases emitted by the exhaust of an internal combustion engine under normal operation. (ORC 4513.22.)

337.21 REAR-VIEW MIRROR; CLEAR VIEW TO FRONT, BOTH SIDES AND REAR.

Every motor vehicle and motorcycle shall be equipped with a mirror so located as to reflect to the operator a view of the street to the rear of such vehicle or motorcycle. Operators of vehicles and motorcycles shall have a clear and unobstructed view to the front and to both sides of their vehicles or motorcycles and shall have a clear view to the rear of their vehicles or motorcycles by mirror. (ORC 4513.23.)

337.22 SIGN OR POSTER UPON WINDSHIELD; WINDSHIELD WIPER.

(a) No person shall drive any motor vehicle, other than a bus, with any sign, poster or other nontransparent material upon the front windshield, sidewings, side or rear windows of such vehicle other than a certificate or other paper required to be displayed by law, except that there may be in the lower righthand corner of the windshield a sign or poster not to exceed four (4) inches in height by six (6) inches in width.

(b) The windshield on every motor vehicle shall be equipped with a device for cleaning rain, snow or other moisture from the windshield, which device shall be maintained in good working order and so constructed as to be controlled or operated by the operator of the vehicle. (ORC 4513.24.)

337.23 LIMITED LOAD EXTENSION ON LEFT SIDE OF PASSENGER VEHICLE.

No passenger-type vehicle shall be operated on a street with any load carried on such vehicle which extends more than six (6) inches beyond the line of the fenders on the vehicle's left side. (ORC 4513.30.)

337.24 MOTOR VEHICLE STOP LIGHTS.

Every motor vehicle, trailer, semi-trailer, and pole trailer when operated upon a highway shall be equipped with two or more stop lights, except that passenger cars manufactured or assembled prior to January 1, 1967, motorcycles, and motor-driven cycles shall be equipped with at least one stop light. Such stop lights when actuated shall emit a red light visible from a distance of five hundred (500) feet to the rear, provided that in the case of a train of vehicles only the stop lights on the rear-most vehicle need be visible from the distance specified.

Such stop lights when actuated shall give a steady warning light to the rear of a vehicle or train of vehicles to indicate the intention of the operator to diminish the speed of or stop a vehicle or train of vehicles.

When stop lights are used as required by this Section, they shall be constructed or installed so as to provide adequate and reliable illumination and shall conform to the appropriate rules and regulations established under Ohio R.C. 4513.19.

(Ord. No. 71-02. Passed 7/08/02.)

Historical motor vehicles as defined in Ohio R.C. 4503.181 are not subject to this Section. (ORC 4513.071.)

337.25 AIR CLEANER REQUIRED.

(a) No person shall operate a motor vehicle with an internal combustion engine unless the carburetion system of the vehicle is protected with an air filter, a flame arresting device, or any other accepted method of protection that is adequate for this purpose. If the original device or system is replaced, it shall be replaced with one that is equal to or better than the original equipment.

(b) This Section does not apply to a person doing automotive repair work on a motor vehicle that necessitates this device being removed while the work is performed.

337.26 MATERIALS USED IN WINDSHIELDS AND WINDOWS, EXCEPTIONS

(a) The Director of highway safety, in accordance with Chapter 119 of the Revised Code, shall adopt rules governing the use of tinted glass, and the use of transparent, nontransparent, translucent, and reflectorized materials in or on motor vehicle windshields, side windows, sidewings, and rear windows that prevent a person of normal vision looking into the motor vehicle from seeing or identifying persons or objects inside the motor vehicle.

(b) The rules adopted under this section may provide for persons who meet either of the following qualifications:

- (1) On the effective date of this section or of any rule adopted under this section, own a motor vehicle that does not conform to the requirements of this section or of any rule adopted under this section;
- (2) Establish residency in this state and are required to register a motor vehicle that does not conform to the requirements of this section or of any rule adopted under this section

(c) No person shall operate, on any highway or other public or private property open to the public for vehicular travel or parking, lease, or rent any motor vehicle

that is registered in this state unless the motor vehicle conforms to the requirements of this section and of any applicable rule adopted under this section.

(d) No person shall install in or on any motor vehicle, any glass or other material that fails to conform to the requirements of this section or of any rule adopted under this section.

(e) No used motor vehicle dealer or new motor vehicle dealer, as defined in section 4517.01 of the Revised Code, shall sell any motor vehicle that fails to conform to the requirements of this section or of any rule adopted under this section.

(f) No reflectorized materials shall be permitted upon or in any front windshield, side windows, sidewings, or rear window.

(g) This section does not apply to the manufacturer's tinting or glazing of motor vehicle windows or windshields that is otherwise in compliance with or permitted by federal motor vehicle safety standard number two hundred five. (ORC 4513.241)

337.99 PENALTY.

(EDITOR'S NOTE: See Section 303.99 for misdemeanor classifications and penalties.)